THE ART AND SCIENCE OF DEFIBRILLATION™

# Lifeline VIEW

## Lifeline VIEW Semi-Automatic Defibrillator

FULL-COLOR VIDEO INSTRUCTION DELIVERS BREAKTHROUGH EASE-OF-USE

The Lifeline VIEW makes it easy for anyone — from first responders to untrained bystanders— to respond confidently and appropriately during an emergency. This revolutionary life-saving device combines a sleek, user-friendly design with military-grade specifications—including the most proven biphasic waveform. It's also the first and only AED with a full-color interactive display that shows step-by-step videos for performing CPR, rescue breathing and external defibrillation.

You can also be confident that the device will be easy to maintain and rescue ready. The Lifeline VIEW provides clear guidance for using and maintaining the device. Additionally, it has been designed to support upgrades and enhancements.

Like the original award-winning Defibtech AED, the Lifeline VIEW includes all the mission-critical features necessary to provide the most advanced cardiac treatment and exceeds the American Heart Association performance recommendations.

defibtech
Life-Saving Technology Within Reach

Defibtech, LLC I 741 Boston Post Road, Guilford, CT 06437 I www.defibtech.com
866-DEFIB-4U (866-333-4248) or 203-453-4507

# Lifeline VIEW Semi-Automatic Defibrillator

TECHNICAL SPECIFICATIONS*

## DEFIBRILLATOR

**TYPE**
Semi-Automatic external defibrillator

**MODEL**
DDU-2300 series

**WAVEFORM**
Biphasic Truncated Exponential
(Impedance compensated)

**ENERGY**
Adult: 150 Joules
Child / Infant: 50 Joules
(Nominal into 50 Ohm load)

**CONTROLS**
Lighted On/Off button
Lighted Shock button

**CHARGE TIME****
Less than 4 seconds
(shock decision to shock)

**DISPLAY**
High-resolution color LCD

**VIDEO PROMPTS**
Full motion video
On-screen text prompts

**CPR COACHING**
Video and voice coaching
On-demand video help

**VOICE PROMPTS**
Extensive voice prompts guide user through operation of the unit

**RESCUE PROTOCOL**
AHA 2005
Supports protocol updates by the user (password protected)

**Typical, with new battery at 25° C

## PATIENT ANALYSIS SYSTEM

**PATIENT ANALYSIS**
Automatically evaluates patient impedance for proper pad contact. Monitors signal quality and analyzes patient ECG for shockable/ non-shockable rhythms.

**SENSITIVITY/SPECIFICITY**
Meets AAMI-DF-80 specifications and AHA recommendations

## BATTERY PACK

**MODEL**
DBP-2003

**POWER**
12V, 2800 mAh

**TYPE**
Lithium/Manganese Dioxide
Disposable, recyclable, non-rechargeable

**CAPACITY****
125 shocks or 8 hours continuous operation

**STANDBY LIFE****
4 years

**LOW BATTERY INDICATORS**
Visible
Audible

**Typical, with new battery at 25° C

## SELF TESTS

**AUTOMATIC**
Automatic daily, weekly and monthly circuitry tests

**BATTERY INSERTION**
System integrity test on battery insertion

**PAD PRESENCE**
Pads preconnected tested daily

**USER-INITIATED**
Unit and battery pack system test initiated by the user

**STATUS INDICATION**
Visual and audible indication of unit status

**STATUS SCREEN**
Unit self-test results
Pads and battery information (status and expiration)

## DEFIBRILLATION / MONITORING PADS

**MODEL**
Adult – DDP-2001
Child / Infant – DDP-2002

**TYPE**
Pre-connected, single-use, non-polarized, disposable, self-adhesive electrodes with cable and connector

**SURFACE AREA**
77 $cm^2$ (nominal, each pad)
50 $cm^2$ (nominal, each pad)

## EVENT DOCUMENTATION

**INTERNAL EVENT RECORD**
Critical ECG segments and rescue event parameters are recorded (greater than 60 minutes) and can be downloaded to a removable data card

**PC-BASED EVENT REVIEW**
ECG with event tag display, and audio playback when available

**REMOVABLE STORAGE**
(optional) Up to 30 hours of ECG and event data storage (no audio option) or up to 3 hours of audio (audio option). ECG and event storage on a removable data card. Actual length of storage is dependent on card capacity.

**USB PORT**
Event download and maintenance operations

## ENVIRONMENTAL

**TEMPERATURE**
Operating: 0 to 50°C (32 to 122°F)
Standby: 0 to 50°C (32 to 122°F)

**RELATIVE HUMIDITY**
Operating / Standby: 5%-95% (non-condensing)

**ALTITUDE**
-500 to 15,000 ft (-150 to 4500 m) per MIL-STD-810F 500.4 Procedure II

**VIBRATION**
Ground (MIL-STD-810F 514.5 Category 20)

Helicopter (RTCA/DO-160D, Section 8.8.2, Cat R. Zone 2, Curve G)

Jet Aircraft (RTCA/DO-160D Section 8. Cat H, Zone 2, Curves B & R)

**SHOCK / DROP ABUSE TOLERANCE**
MIL-STD-810F 516.5 Procedure IV
48 inches (1.2 meters), any edge, corner, or surface, in standby mode

**CRUSH TEST**
1,000 pounds (450 kg)

**SEALING / WATER RESISTANCE**
IEC60529 class IP55; Protected against dust and waterjets (battery pack installed)

**ESD**
EN61000-4-2: (Open air up to 8kV or direct contact up to 6kV)

**EMC (Emission)**
CISPR 11 Group 1 Level B and FCC Part 15

**EMC (Immunity)**
IEC 61000-4-3 and IEC 61000-4-8

## PHYSICAL

**SIZE**
7.3 x 9.5 x 2.3 Inches
(18.5 x 24 x 5.8 cm)

**WEIGHT**
Less than 3 lbs (1.4 kg)
(with battery)

*Specifications subject to change without notice

0197

defibtech
Life-Saving Technology Within Reach

Defibtech, LLC • Guilford, CT 06437 1-203-453-4507
1-866-DEFIB-4U (866-333-4248) • www.defibtech.com

DAC-2703-AE rev A